

Solving Quadratic Assignment Problem Using Forward and Backward Exchange Algorithm

by Faiz Ahyaningsih

Submission date: 04-Mar-2021 01:08AM (UTC-0800)

Submission ID: 1523957675

File name: GJPAM.pdf (437.95K)

Word count: 3148

Character count: 15406

Solving Quadratic Assignment Problem Using Forward and Backward Exchange Algorithm

Faiz Ahyaningsih

*State University of Medan, Department of Mathematics,
Jl. Willem Iskandar Psr V Medan Estate Medan 20221, Indonesia.*

Abstract

Quadratic assignment problem is one of the combinatorial optimization problems of deciding the placement of facilities in specified locations in such a way as to minimize a nonconvex objective function expressed in terms of flow between facilities, and distance between location. Since QAP is NP-hard problem, and even finding an ε -approximate solution is a difficult problem, therefore to get a 'good' starting point is necessary, in order to obtain a better optimal solution. In this paper we propose a random point strategy to get initial starting point and then use forward exchange algorithm and backward exchange algorithm to get 'optimal' solution. As a computational experience we solved the problem of Had12, Esc 16b, Esc 16c and Esc 16h from QAPLIB. Finally, we present a comparative study between our proposed algorithm and Data -Guided Lexisearch Algorithm. The computational study shows the effectiveness of our proposed algorithm.

Keywords: Backward Exchange Algorithm, Forward Exchange Algorithm, Quadratic Assignment Problem, Random Point Strategy,

INTRODUCTION

Quadratic assignment problem (QAP) is in simplest form concerned with locating facilities on locations, such that total transportation costs are minimized. The transportation cost incurred by locating two facilities is proportional both to the flow of transportation between the facilities and the distance between their locations. In 1957 QAP was introduced by Koopmann and Beckmann as a mathematical model related to economic activities. The QAP however is not only nonlinear but also not unimodal, so many researches attracted to investigate this problem. An heuristic yielding a good solution seems a more appropriate course of action than attempting an

optimal solution, and many of the papers aim at achieving improvements to an initial assignment.

The QAP has been applied to many fields such as backboard wiring, typewriter keyboards and control panel design, scheduling, numerical analysis, storage-and-retrieval, and many others. One of the oldest applications of the QAP is the assignment of specialized rooms in a building (Elshafei, 1977). In this case, a_{ij} is the flow of people that must go from service i to service j and b_{ij} is the time for going from room i to room j . The other one is application in turbine runner balancing (Laporte and Mercure, 1988). A recent application is the assignment of gates to airplanes in an airport (A. Bouras *et al.*, 2014); in this case, a_{ij} is the number of passengers going from airplane i to airplane j (a special “airplane” is the main entrance of the airport) and b_{kl} is the walking distance between gates k and l .

LITERATURE REVIEW

The QAP was one of the first problems solved by metaheuristics methods first conceived in the 1980's. Burkard and Rendl (1984) proposed a simulated annealing procedure that was able to find much better solutions than all the previously designed heuristic methods. Six years later, Connolly (1990) proposed an improved annealing scheme. His method is easy to set up, since the user has to select the number of iterations; and all other parameters are automatically computed. At around the same time, Skorin-Kapov (1990) proposed a tabu search. Then, Taillard (1991) proposed a more robust tabu search, with fewer parameters and running n times faster than the previous implementation. Even though Taillard's method was proposed over 24 years ago, it remains one of the most efficient for some problem instances. In 1992 Hadley *et al.* propose a new lower bound (Hadley *et al.*, 1992), two years later Battiti and Tecchiolli proposed the reactive tabu search (Battiti and Tecchiolli, 1994a), also the comparison of tabu search techniques and simulated annealing (Battiti and Tecchiolli, 1994b), then the star-shape diversification approach of Sondergeld and Voss (1996). Recent T. James *et al.* (2007), addressed a multi-start tabu search and diversification strategies for the QAP.

Genetic algorithms have also been proposed, for instance by Tate and Smith (1995), but hybrid approaches, such as those of Fleurent and Ferland (1994), Ahuja *et al.* (2000), Drezner (2002a, 2002b), are more efficient. Another heuristic, GRASP (greedy randomized adaptive search procedure) was proposed by Li, Pardalos and Resend (1994). An ant colony system approaches by Taillard (1998), Gambardella *et al.*, (1999), Stutzle and Hoos 1999,) have been proposed, as well as a scatter search (Cung *et al.*, 1997). Some of these methods have been compared in Taillard (1995) who showed that the efficiency of these methods strongly depends on the problem instance type to which they are applied.

In 2005 Ahyaningsih *et al.* proposed some new results and generalizations for QAP (2005), then in 2006 Ahyaningsih proposed improved strategy for solving QAP (2006). Recently, Ahmed ZH., (2011a) proposed a data-guided lexisearch algorithm

(DGLSA) for the asymmetric traveling salesman problem. Still in this year, Ahmed ZH., (2011b) solved the bottleneck travelling salesman problem using DGLSA. In 2014 Ahmed ZH solved QAP using DGLSA, (2014). One year later Ahyaningsih and Sitompul proposed a combined strategy for solving QAP (2015).

FORMULATION OF QUADRATIC ASSIGNMENT PROBLEM

QAP is combinatorial problem of deciding the placement of facilities in specified locations in such a way as to minimise a quadratic objective function. Consider the problem of locating n facilities in n given locations. If the flow f_{ik} between each pair of facility i and facility k and the unit transportation cost (or distance) d_{jl} between locations j and l are known, then the problem is defined to be

$$\text{minimize } \Phi = \frac{1}{2} \sum_{i=1}^n \sum_{k=1}^n \sum_{j=1}^n \sum_{l=1}^n f_{ik} d_{jl} x_{ij} x_{kl}$$

$$\text{subject to } \begin{aligned} \sum_{j=1}^n x_{ij} &= 1 & i = 1, \dots, n \\ \sum_{i=1}^n x_{ij} &= 1 & j = 1, \dots, n \\ 0 &\leq x_{ij} \leq 1 \\ x_{ij} &\text{ integer} \end{aligned}$$

Matrices $[f_{ik}]$ and $[d_{jl}]$ are assumed to be symmetric. The assignment variable x_{ij} has a value 1 if facility i is at location j , and is zero otherwise. The constraints reflect the fact that each location can be assigned to only one facility, and each facility can be assigned to only one location.

Generally the QAP is a non-convex problem so any solution obtained will necessarily be a local optimum and not a global optimum.

ALGORITHM FOR SOLVING QAP

Since the quadratic form may be non-convex, the chances of obtaining a good integer feasible solution are considerably enhanced by paying some attention to the starting point for the search procedure.

In this case we create a computer program that would generate a random assignment. Then we calculate the value of objective function using this random assignment. In order to get a good initial starting point it is necessary to input an arbitrary value of objective function θ enough big say $\theta = 10000000$, so its value always greater than $\bar{\theta}$, at last from a numbers of iteration θ_{min} will be reached, match to the assignment x_i . Input x_i to the objective function θ in forward exchange algorithm and backward

exchange algorithm. This process repeated according to the number of iteration. The last θ_{min} will be reached.

The steps used to get a random initial starting point are written as follows :

1. Read $\theta = 10000000$, matrix $[f_{ik}]$ dan $[d_{jl}]$, $n =$ problem dimension and $ITEM$ as the number of iteration, $a = 1$
2. Generate random permutation, $x_i = \text{randperm}(n)$; for every facility $i, i = 1, 2, \dots, n$.
3. $x_{ij} = 1$ for gen $x_i = j$; $x_{ij} = 0$ for generate $x_i \neq j$; $i, j = 1, 2, \dots, n$
4. Calculate the objective function value

$$\bar{\theta} = \sum_{i=1}^n \sum_{k=1}^n \sum_{j=1}^n \sum_{l=1}^n f_{ik} d_{jl} x_{ij} x_{kl}$$
5. if $\bar{\theta} < \theta$, then $\theta = \bar{\theta}$; $a = a + 1$
6. if $a < ITEM$, back to (2)
7. STOP

Forward Exchange Algorithm:

1. Input n as problem dimension.
2. Read flow matrix $[f_{ik}]$, distance matrix $[d_{je}]$, initial assainment $[x_{ij}]$
3. Calculate $\theta = \sum_{i=1}^n \sum_{k=1}^n \sum_{j=1}^n \sum_{l=1}^n f_{ik} d_{jl} x_{ij} x_{kl}$
4. Generate $x_i = j$ for $x_{ij} = 1$; $i, j = 1, \dots, n$
5. $a = 1$
6. $b = 1$
7. $c = \text{Gen } x_{i=a}$; $\text{Gen } x_{i=a} = \text{Gen } x_{i=a+b}$; $\text{Gen } x_{i=a+b} = c$
8. $x_{ij} = 1$ for $\text{Gen } x_i = j$, $x_{ij} = 0$ for $\text{Gen } x_i \neq j$, $i, j = 1, \dots, n$
9. Calculate objective function

$$\bar{\theta} = \sum_{i=1}^n \sum_{k=1}^n \sum_{j=1}^n \sum_{l=1}^n f_{ik} d_{jl} x_{ij} x_{kl}$$
10. if $\bar{\theta} < \theta$ then $\theta = \bar{\theta}$ go to (14)

11. Gen $x_{i=a+b} = \text{Gen } x_{i=a}; \text{ Gen } x_{i=a}=c$
12. $b = b+1$
13. if $b \leq n - a$ go to (7)
14. $a = a+1$
15. if $a \leq n$ go to (6)
16. STOP

Backward Exchange Algorithm :

1. Input n as problem dimension
2. Read flow matrix [f_{ik}], distance matrix [d_{je}], initial assignment $X = [x_{ij}]$
3. Calculate $\theta = \sum_{i=1}^n \sum_{k=1}^n \sum_{j=1}^n \sum_{l=1}^n f_{ik} d_{jl} x_{ij} x_{kl}$
4. Gen $x_{i=j}$, for $x_{ij}=1; i, j = 1, \dots, n$
5. $a = n$
6. $b = n$
7. $c = \text{Gen } x_{i=a}; \text{ Gen } x_{i=a} = \text{Gen } x_{i=b}; \text{ Gen } x_{i=b} = c$
8. $x_{ij}=1$ for Gen $x_{i=j}$, $x_{ij}=0$ for Gen $x_{i \neq j}$, $i, j=1, \dots, n$
9. Calculate objective function

$$\bar{\theta} = \sum_{i=1}^n \sum_{k=1}^n \sum_{j=1}^n \sum_{l=1}^n f_{ik} d_{jl} x_{ij} x_{kl}$$

10. if $\bar{\theta} < \theta$ then $\theta = \bar{\theta}$ go to (14)
11. Gen $x_{i=b} = \text{Gen } x_{i=a}; \text{ Gen } x_{i=a}=c$
12. $b = b-1$
13. if $b \geq a + 1$ go to (7)
14. $a = a-1$
15. if $a > 1$ go to (6)
16. STOP

COMPUTATIONAL EXPERIENCE

To run the program we use laptop with processor Intel (R) core (TM) i3-3217U, CPU 1.80 GHz RAM 4.00 GB.

12 × 12 Problem :

The 12 × 12 QAP is adopted from Hadley (1992). This is a large scale problem with 144 binary variables. To solve the problem, we input n as dimension of problems, number of iteration, matrix flow [f_{ik}] and matrix distance [d_{je}]. In each iteration we use random point strategy to get the initial assignment of the QAP and then we use forward exchange strategy and backward exchange strategy to get the integer feasible solution.

We try many kind of iterations.

The result can be seen in table 1 below.

Table 1. The Search Table for Had12

Number of Iteration	Objective Value	Permutation	Running Time (Second)
500	1660	3 10 11 2 12 7 5 1 8 6 4 9	57.997902
600	1664	3 10 2 12 11 5 6 7 8 1 4 9	70.160402
700	1660	3 10 12 2 11 5 6 7 8 1 4 9	81.361419
750	1654	3 10 11 2 12 5 7 6 8 1 9 4	86.357992
800	1654	8 10 2 11 12 5 6 7 3 1 4 9	92.285597
850	1654	8 10 2 11 12 5 7 6 3 1 4 9	99.568710
900	1656	3 10 5 2 12 11 7 1 8 6 4 9	104.039284
950	1656	3 10 5 2 12 11 7 1 8 6 4 9	110.342666
1000	1660	3 10 11 2 12 6 5 1 8 7 4 9	117.018335
1050	1652(OPT)	3 10 11 2 12 5 6 7 8 1 4 9	122.512347

From table 1 we can conclude :

1. By the increasing of number iteration, the objective value approach to the optimum value.
2. On iteration 1050 the optimum value was reached, as reported on QAPLIB.
3. There is a number of iteration have same objective value but different permutation (just in case, based on the matrix flow [f_{ik}] and matrix distance [d_{je}])

16 x 16 Problem :

The 16 × 16 QAP is adopted from Escermann (1990). This is a large scale problem with 256 binary variables. We try the number of iteration is 500, no other number of iteration, because by using this number of iteration we found the optimal solution according to the QAPLIB, Burkard, *et. al.* (1997).

The result can be seen in table 2 below.

Table 2. The Search Table for Esc16

Instance	Number of Iteration	Objective Value	Permutation	Running Time (Second)
Esc 16b	500	292 (OPT)	2 3 16 9 7 13 1 5 15 11 14 4 12 8 10 6	371.654879
Esc 16c	500	160 (OPT)	5 16 15 8 7 6 11 3 4 9 2 10 12 14 1 13	270.088915
Esc 16h	500	996 (OPT)	16 15 8 5 14 9 10 6 1 2 13 4 3 11 12 7	326.956387

If we compare our proposed algorithm and Data-Guided Lexisearch Algorithm (DGLSA) by Ahmed (2014), the result showed in table 3 :

Table 3. The Comparison of DGLSA and Our Proposed Algorithm

Instance	BKV	DGLSA			Our Proposed Algorithm		
		BSV	Error (%)	Running Time (Second)	BSV	Error (%)	Running Time (Second)
Esc 16b	292	292	0.00	14400.00	292	0.00	371.654879
Esc 16c	160	160	0.00	2984.60	160	0.00	270.088915
Esc 16h	996	996	0.00	1298.50	996	0.00	326.956387

BKV = Best known value (from QAPLIB)

BSV = Best solution value

Error = { (BSV-BKV)/BKV } x 100%

From table 3 we show that our proposed methods much more better than Data-Guided Lexisearch Algorithm (DGLSA).

CONCLUSION

For size problem 12 optimum value reached at iteration 1050, meanwhile for size problem 16 optimum value reached at iteration 500 (it caused matrix Esc16 more simple then matrix Had12 (as can be seen from QAPLIB), so the problem not only based on the size but also on the matrix itself).

Generally, the greater problem instance the greater number of iteration, but in this case not like that.

Overall the procedure described here has proved successful in obtaining integer feasible solution to the Quadratic Assignment Problem in relatively short computing times (as can be seen from the running time).

REFERENCES

- [1] A.N.Elshafei, 1977, "Hospital lay-out as a quadratic assignment problem ", *Operational Research Quaterly*, 28, 167-179
- [2] G.Laporte and H.Mercure, 1998, "Balancing hydraulic turbine runners: A quadratic assignment problem ", *EJOR* 35, 378-381
- [3] A. Bouras, M. A. Ghaleb, U. S. Suryahatmaja, and A. M. Salem, 2014, "The Airport Gate Assignment Problem: A Survey," *e Scientific World Journal*, Volume 2014, Article ID 923859
- [4] R.E.Burkard, and F.Rendl, 1984, "A thermodynamically motivated simulation procedure for combinatorial optimization problems," *European Journal of Operational Research* 17, 169-174
- [5] D.T.Connoly, 1990, "An improved annealing scheme for the QAP", *European Journal of Operational Research* 46, 93-100
- [6] J.Skorin-Kapov, 1990, "Tabu search applied to the quadratic assignment problem", *ORSA Journal on Computing* 2, 33-45
- [7] E.D.Taillard, 1991, "Robust tabu search for the quadratic assignment problem ", *Parallel Computing* 17, 443-455 S. W. Hadley, F. Rendl and H. Wolkowicz, " A New Lower Bound Via Projection for the Quadratic Assignment Problem", *Mathematics of Operation Research* 17, 727-739 (1992)
- [8] S. W. Hadley, F. Rendl and H. Wolkowicz, 1992, " A New Lower Bound Via Projection for the Quadratic Assignment Problem", *Mathematics of Operation Research* 17, 727-739
- [9] R.Battiti and G.Tecchiolli, 1994a, "The reactive tabu search ", *ORSA Journal on Computing* 6, 126-140
- [10] R.Battiti and G.Tecchiolli, 1994b, "Simulated annealing and tabu search in the long run: a comparison on QAP Tasks ", *Computers and Mathematics with Applications*, 28, 1-8
- [11] L.Sondergeld and S.Vob, 1996, "A star-shaped diversification approach in Tabu search ", in: "Meta-heuristics: Theory and Applications", I.H.Osman and J.P.Kelly (eds.), Kluwer academic Publishers, 489-502
- [12] T. James, C. Rego, and F. Glover, 2007, " Multi-start tabu search and diversification for the quadratic assignment problem", Technical Report, Virginia Tech, Blacksburg, VA
- [13] D.E. Tate and A.E.Smith, 1995, "A genetic approach to the quadratic assignment problem ", *Computers and Operations Research* 1, 855-865
- [14] C.Fleurent and J.Ferland, 1994, "Genetic hybrids for the quadratic assignment problem ", *DIMACS Series in Math. Theoretical Computer Science* 16, 190-206

- [15] R. K. Ahuja, J.B.Orlin, and A.Tiwari, 2000, “ A Descent Genetic Algorithm for the Quadratic Assignment Problem”, *Computers and Operations Research* 27,917-934
- [16] Z. Drezner, 2002a, “A New Genetic algorithm for the Quadratic Assignment Problem “, *INFORMS Journal on Computing*
- [17] Z. Drezner, 2002b, “Robust Heuristic Algorithm for the Quadratic assignment Problem “, *EJOR*
- [18] Y.Li, P.M.Pardalos, and M.G.C.Resende, 1994, “A randomized adaptive search procedure for the quadratic assignment problem”, in “Quadratic Assignment and Related Problems”, P.Pardalos and H. Wolcovicz (eds.), DIMACS series in Discrete mathematics and Theoretical Computer Science, 16, 237-261
- [19] E.D.Taillard, 1998,“FANT:Fast ant system “, Technical report IDSIA-46-98, IDSIA, Lugano
- [20] L.M.Gambardella, E.D.Taillard and M.Dorigo, 1999, “Ant colonies for the quadratic assignment problem “, *Journal of the Operational Society* 50, 167-176
- [21] T.Stutzle and H..Hoos, 1999, “the Max-Min ant system and local search for combinatorial optimization problems: Towards adaptive Tools for Global Optimization” ;, in : “Meta-heuristics: Advances and Trends in Local Search Paradigms for Optimization”, S.Voss, S.Martello, I.H.Osman, C.Roucairol (eds.), Kluwer academic Publishers, 313-329
- [22] V.-D, Cung, T.Mautor, P.Michelon, and A. Tavares, 1997,“A scatter search based approach for the quadratic assignment problem”, proceedings of the IEEE International Conference on Evolutionary Computation and Evolutionary Programming (ICEC’97),Indianapolis, 165-170
- [23] E.D.Taillard, 1995, “Comparison of iterative searches for the quadratic assignment problem “, *Location Science* 3, 87-105
- [24] F. Ahyaningsih, Raidani, A.H. Nasution, and H. Mawengkang, 2005, “The Quadratic Assignment Problem : Some New Results and Generalizations”, *Proceeding of the 1st IMT-GT, RCMSA, Prapat Indonesia*
- [25] F. Ahyaningsih, S. Suwilo, and H. Mawengkang, 2006 , “an Improved Strategy for Solving Qudratic Assignment Problem”, *Proceeding of the 2st IMT-GT, RCMSA, Penang Malaysia*
- [26] Z. H. Ahmed, 2011a, “A data-guided lexisearch algorithm for the asymmetric traveling salesman problem”, *Mathematical Problems in Engineering*, doi:10.1155/2011/750968
- [27] Z. H. Ahmed, 2011b, “A data-guided lexisearch algorithm for the bottleneck travelling salesman problem”, *International Journal of Operational Research*, 12(1), 20–33
- [28] Z. H. Ahmed, 2014, “A Data-guided Lexisearch Algorithm for the Quadratic Assignment Problem”, *Indian Journal of Science and Technology*, Vol 7(4), 480-490
- [29] F. Ahyaningsih and O. S. Sitompul, 2015, “Developing A Combined Strategy For Solving Quadratic Assignment Problem,” *International Journal Of Scientific& Technology Research*, Vol 4 Issue 11, November Edition, ISSN 2277-8616 : 297-301.

- [30] B. Eschermann, and H. J. Wunderlich, 1990, "Optimized Synthesis of Self-Testable Finite State Machines," in 20th International Symposium on Fault-Tolerant
- [31] R. E. Burkard, Karisch SE, Rendl F, 1997, " QAPLIB - a quadratic assignment problem library," J Global Optim. 10(4), 391–403

Solving Quadratic Assignment Problem Using Forward and Backward Exchange Algorithm

ORIGINALITY REPORT

19%

SIMILARITY INDEX

13%

INTERNET SOURCES

21%

PUBLICATIONS

6%

STUDENT PAPERS

PRIMARY SOURCES

- | | | |
|---|---|----|
| 1 | aasec.conference.upi.edu
Internet Source | 4% |
| 2 | Kuan Yew Wong. "A genetic ant colony optimisation system (GenANT) for quadratic assignment problems", International Journal of Mathematics in Operational Research, 2009
Publication | 3% |
| 3 | Mahdi Bashiri, Hossein Karimi. "An analytical comparison to heuristic and meta-heuristic solution methods for Quadratic Assignment Problem", The 40th International Conference on Computers & Industrial Engineering, 2010
Publication | 2% |
| 4 | "Parallel Processing of Discrete Problems", Springer Science and Business Media LLC, 1999
Publication | 2% |
| 5 | H. Mawengkang, B. A. Murtagh. "Solving nonlinear integer programs with large-scale | 2% |

optimization software", Annals of Operations Research, 1986

Publication

6

Huizhen Zhang, Cesar Beltran-Royo, Liang Ma. "Solving the quadratic assignment problem by means of general purpose mixed integer linear programming solvers", Annals of Operations Research, 2012

Publication

2%

7

www.indjst.org

Internet Source

1%

8

kluedo.ub.uni-kl.de

Internet Source

1%

9

technodocbox.com

Internet Source

1%

10

Éric D. Taillard. "Comparison of iterative searches for the quadratic assignment problem", Location Science, 1995

Publication

1%

11

Sukono, Betty Subartini, Susi, Sudradjat Supian, Herlina Napitupulu, Ruly Budiono, Hafizan Juahir. " Modeling of the impact of GDP and human population on CO emission by using Cobb-Douglas model and particle swarm optimization ", IOP Conference Series: Earth and Environmental Science, 2019

Publication

1%

Exclude quotes On

Exclude matches < 1%

Exclude bibliography On

Solving Quadratic Assignment Problem Using Forward and Backward Exchange Algorithm

GRADEMARK REPORT

FINAL GRADE

/0

GENERAL COMMENTS

Instructor

PAGE 1

PAGE 2

PAGE 3

PAGE 4

PAGE 5

PAGE 6

PAGE 7

PAGE 8

PAGE 9

PAGE 10
